

MERLIN

U S A

MADE TO MEASURE®
ORDER FORM

2

()

()

1



TABLE OF CONTENTS

- 3)...Your Personal Information
- 4)...MERLIN DEALER INFORMATION
- 5)...Your Riding Preferences
- 6)...YOUR CURRENT BICYCLE MEASUREMENTS
- 7)...ABOUT YOUR NEW BIKE
- 8)...STANDARD DIMENSIONS (ALL FRAMES)
- 9)...ABOUT WHEEL SIZES

INSTRUCTIONS

EACH MERLIN IS BUILT TO FIT YOU PERFECTLY. HELP US TO HELP YOU BUY THE RIGHT BIKE.

- 1)...PRINT THE FORM
- 2)...FILL IT OUT.
- 3)...RETURN IT TO THE DEALER.



YOUR PERSONAL INFORMATION

PLEASE PRINT

Name	
Address	
CITY	STATE
Day Phone	Evening Phone
FAX LINE	EMAIL
SEX	WEIGHT
Cycling Shoe Size	SHOULDER WIDTH
Arm Length	THIGH LENGTH



MERLIN DEALER INFORMATION

PLEASE PRINT

Dealer Name		
CONTACT NAME		
Address		
Сіту	STATE	ZIP
Day Phone	FAX LINE	
WEB SITE	EMAIL	



YOUR RIDING PREFERENCES

PLEASE CHECK ALL THAT APPLY.

Road Racing	Long Distance Tours	Prefer Fast Steering
Criterium Racing	Miles Per Day	Prefer "No-Hands" Steering
Time Trials	Miles Per Week	Prefer Stiff Ride
Triathlons	Pedal Through Corners	Prefer Soft Ride
Long Recreational Rides	Coast Through Corners	Toe Clip Overlap Ok
Short to Mid-distance Rides	Usually Climb Standing	No Toe Clip Overlap
Short Distance Tours	Usually Climb Seated	



YOUR CURRENT BICYCLE MEASUREMENTS

PLEASE CHECK ALL THAT APPLY.

(A) Seat Tube Length	(B) Top Tube Length
Center of Bottom Bracket to Top of Tube	Center of Seat Tube to Center of Head Tube
(C) STEM LENGTH	(D) SEAT TUBE ANGLE
Center to Center	If Known
(=) C	
(E) SADDLE POSITION	(F) SADDLE POSITION
On Post, Fore	On Post, Aft
(C) SEATBOOT LEMOTH	(H) Chank I faction
(G) Seatpost Length	(H) Crank Length
Above Cluster	
(I) Saddle Brand	(J) Seatpost Brand
(I) SADDLE DRAND	()/ SEATTOST DRAND



Merlin Made to Measure® Order Form ABOUT YOUR NEW BICYCLE

TIRE SIZE	FORK BRAND & LENGTH
REAR AXLE SPACING (mm)	FORK RAKE
Freewheel Range	Stem Brand & Length
Crankset	BAR BRAND Model & Width
Crank Length	HEADSET (1-1/8"-inch)
Chainwheel Gearing	SEATPOST (27.2 mm)
Pedal Brand & Model	Saddle Brand & Model
If you already know the dimensions you want for your n (seat tube length) from the center of the bottom bracke	to center of dropout; assumed to be 370 mm for a 700C wheel. ew frame, please supply them below. Measure the frame size to the top of the top tube, as shown under "Current Bicycle to center. Use inches or centimeters, whichever is easier.
FRAME SIZE, CENTER TO TOP	TOP TUBE *ctr - ctr
ROP OR BOTTOM BRACKET HEIGHT	HEAD TUBE ANGLE *degrees
SEAT TUBE ANGLE *degrees	FORK RAKE *ctr - ctr
HAINSTAY LENGTH *ctr - ctr	*Or setback in mm (centerline of bottom bracket to centerline of seat cluster



STANDARD DIMENSIONS-ALL FRAMES

All Merlins are built to the following standard dimensions:

1-1/8" INCH HEADSET

27.2 - MM SEATPOST; SEATPOST BOLT M6X1

130 - MM AXLE SPACING (UNLESS SPECIFIED IN YOUR BIKE SPECS)

ENGLISH THREADED
68 - MM BOTTOM BRACKET SHELL

VERTICAL DROPOUTS

EYELETS & BOTTLE MOUNTS M5X8



ABOUT WHEEL SIZES

Our road frames our usually sized for 700C wheels.

Frames smaller than 49cm will be built with 650c

Wheels unless you specify otherwise.

The 650c size is available in both tubular and

Clincher tire styles, and is commonly called 26-inch road.

The nominal bead seat diameter is 584mm.

Most 26-inch road forks are sized for 650c wheels.

If you would prefer a 26-inch mountain wheel size, be sure to tell your dealer.

These wheels have a nominal bead seat diameter of 559mm.

Note that virtually all forks sized for 26-inch mountain wheels have cantilever brakes. In most cases, you will not be able to adapt caliper brakes to these forks.

IF IN DOUBT, CONSULT YOURDEALER.